



**PCB LAYOUT**

REV	ECN NO	DESCRIPTION	DATE	NAME
A	—	NEW	03/16-'22	Steven

  

PIN	DIM A	DIM B
2x1P	3.04	
2x2P	5.58	2.54
2x3P	8.12	5.08
2x4P	10.66	7.62
2x5P	13.20	10.16
2x6P	15.74	12.70
2x7P	18.28	15.24
2x8P	20.82	17.78
2x9P	23.36	20.32
2x10P	25.90	22.86
2x11P	28.44	25.40
2x12P	30.98	27.94
2x13P	33.52	30.48
2x14P	36.06	33.02
2x15P	38.60	35.56
2x16P	41.14	38.10
2x17P	43.68	40.64
2x18P	46.22	43.18
2x19P	48.76	45.72
2x20P	51.30	48.26
2x21P	53.84	50.80
2x22P	56.38	53.34
2x23P	58.92	55.88
2x24P	61.46	58.42
2x25P	64.00	60.96
2x26P	66.54	63.50
2x27P	69.08	66.04
2x28P	71.62	68.58
2x29P	74.16	71.12
2x30P	76.70	73.66
2x31P	79.24	76.20
2x32P	81.78	78.74
2x33P	84.32	81.28
2x34P	86.86	83.82
2x35P	89.40	86.36
2x36P	91.94	88.90
2x37P	94.48	91.44
2x38P	97.02	93.98
2x39P	99.56	96.52
2x40P	102.10	99.06

  

规范  
Specifications

- 额定电流:3.0安培  
Current Rating: 3.0Amps
- 额定电压:250V AC/DC  
rated voltage: 250V AC/DC
- 绝缘电阻:最小1000 MΩ  
Insulation Resistance: 1000 MΩ Min
- 耐压:500V AC  
Dielectric withstanding Voltage: 500V AC
- 接触电阻:最大20 mΩ  
Contact Resistance: 20 mΩ Max
- 工作温度:-40° C ~ +105° C  
Operating Temperature: -40° C to+105° C
- 接触材质:磷铜  
Contact Material: Phosphor Bronze
- 电镀:金G/F  
Plating: Au G/F
- 绝缘材料:PA6T,UL94V-0黑色  
Insulation Material: PA6T, UL94V-0, Black
- 标有“\*”符号为主要尺寸  
Marked “\*” symbol are major dimensions
- 包装: 卷装  
Packing: Reel

**Ordering Information**

LFH 254 X XX X XXXX

Pitch: 254=2.54  
Rows: 1: 单排, 2: 双排, 3: 三排, 4: 四排  
PIN Number: 1~99 (单排的PIN数)  
Packing: A: 袋装, B: 管装, C: 盘装, D: 卷装, E: 袋加盒, F: 其它  
Serial No: 0001~9999

**LDCONN 东莞连大精密制品有限公司**  
DongGuan LianDa Precision Products Co., LTD

STANDARD TOLERANCE (EXCEPT SPECIFIED)	
LINER	ANGLES
.0 ±0.30	0.° ±3°
.00 ±0.20	.0° ±2°
.000 ±0.10	.00° ±1°

TITLE	PH2.54X5.0 2X10P SMT 双排排母O型 带吸取帽	DRAWN BY	Steven	03/16-'22
PART NO.	LFH254210D0008	CHECKED BY		
DRAWING NO.		APPROVED BY		
SCALE	1:1	UNIT	mm	PAGE 1/1
				SIZE A4